

# ChemGrout CG-050

## Air Powered Grouter



- Lightweight aluminium construction offers portability for confined, hard to reach jobs.
- Ideal for efficient grouting of smaller applications.
- Designed for pumping grout mixes, high viscosity slurries and premixed grouts.
- Delivers up to 5 gpm with pressures to 225 psi (400 psi hydraulic).
- Utilises a 19 litre holding hopper and 2" piston pump.
- Engineered for minimal maintenance with only three wetted and five working parts.
- Quick disconnect couplings allow for rapid disassembly in just seconds for easy maintenance and clean-up.
- The safe, compressed air drive is especially suited for mines, tunnels and remote sites where fuel fumes are dangerous and electricity is unavailable.
- One-man operation saves both time and money.



### APPLICATIONS

- Door & window frames
- Void filling
- Slab raising
- Pavement dowel bars
- Piling encasements
- Machine base & joint grouting
- Waterproofing
- Piling encasements
- Precast tunnel joints
- Concrete floors / roofs

CG-050	Air	Hydraulic
Pump	2" piston	2" piston
Output	5 gpm (19 lpm)	5 gpm (19 lpm)
Pressure	225 psi (16 bar)	400 psi (28 bar)
Weight	25kg	48kg
Requires	15 cfm, 100 psi	5 gpm, 1000 psi
Size	111.76cm x 112.5cm x 60.96cm (L x W x H)	

