



The Giotto Mono is a single-phase plastering machine ideal for dosing, mixing, pumping and spraying dry mix materials from a bag or silo.

Applications:

- Internal plasters: gypsum, gypsum-lime plaster
- External Coatings: lime, lime/cement, ETICS and insulating plaster
- Self-levelling floor screeds.

Features:

- Steel body and highly efficient geared motor
- Universal and Interchangeable components
- Can be disassembled for easy transportation
- Great performance with very low energy consumption.



Turbosol Giotto



Technical Data	Single Phase
Power Supply Tension	230 V
Auxiliary controls tensions	24 V
Motor	3.0 kW plaster pump – 0.25 cell dosing hopper
Worm gear pump	Turbosol D5 2.5 Eco
Max. aggregate size	4 mm
Output*	13 – 16 -18 l/min
Max. working pressure	40 bar
Diaphragm compressor	230 l / min – 0.52 kW
Water Pump	45 l/min - 0.37 kW
Hopper capacity	110 l
Delivery Distance*	20 m
Delivery height	10 m
Filling height	99 cm
Delivery manifold	Ø 25 mm
Size (L x W x H)	115 x 65 x 147 cm
Weight	247 kg

* The data indicated are theoretical and depend on the quality and consistency of the materials to be used, wear and tear of the pump and the diameter of the hoses. The performance in distance and height can not be reached simultaneously.