

# PFT Bolero FC-230V



The handy **PFT BOLERO** is a combination of mixing, pumping and spraying machine.

If material, which is roughed up intensely is to be processed, the new PFT BOLERO is the perfect machine.

In clockwise mode of the mixing shaft the material is mixed continuously. In anti-clockwise mode the pumping machine is connected and pumps the ready mixed material to the place of use.

## ADVANTAGES

- Cost effective, versatile solution for small construction sites
- Combination of mixing, pumping and spraying pump with clockwise and anti-clockwise operation
- Stipulated mixing and mortar source times which can be precisely adhered
- Mixing errors are virtually eliminated
- Light weight and easy to transport
- Mortar pressure gauge integrated
- Safety switch

## APPLICATIONS

Materials which need to be roughed up intensely:

- Reinforcement, adhesive mortars
- Fire protection mortars
- Bentonite
- Structure and acoustic plaster
- Levelling compound and interior primer



## TECHNICAL DATA

Part no.	00 24 53 37
Working pressure	max. 20 bar
Conveying capacity	up to 9 litre / min
Conveying distance	up to 30 m
Motor	230 V, 1 Ph, 50 Hz, 2.2 kW, 181 rpm
Connection cable	BLU 3-16 A   BLU 2-16 A - 25 m
Hopper content	68 litre
Rotor/Stator	D 4-2
Material outflow	DN35 female part
Agitator	BOLERO centro
Dimensions: L/W/H	800/700/1,500 mm
Filling height	950 mm
Weight	~ 112 kg

